



## BE GY16 E VU 5G1,5 Std R1

Preflex 16 mm+H07V-U Eca 5G1.5 G/Y BL BR BLA GR C100

### Properties of the article

|                      |                    |
|----------------------|--------------------|
| ◦ Articulenumber     | 1234000334         |
| ◦ Barcode            | 5420056252263      |
| ◦ Category           | Energy & Light     |
| ◦ Gross weight (kg)  | 14.8               |
| ◦ Dimensions (WxLxH) | 500 X 500 X 200 MM |
| ◦ Packaging          | Roll               |
| ◦ Length             | 100                |

### Properties of the Preflex® tube

|                                 |                         |
|---------------------------------|-------------------------|
| ◦ Material of tube              | Polypropylene           |
| ◦ Color                         | Grey                    |
| ◦ Outer diameter (mm)           | 16                      |
| ◦ Inner diameter (mm)           | 10.6                    |
| ◦ Classification                | ICTA 3422               |
| ◦ Pressure resistance           | 750N / 23°C             |
| ◦ Impact resistance             | 6J / -5°C               |
| ◦ Breakthrough test             | 2000V / 50-60 Hz 15min. |
| ◦ Insulation resistance         | min. 100 Mohm/80cm      |
| ◦ Test temperature              | -5°C tot +90°C          |
| ◦ Min. installation temperature | -5°C                    |

### Characteristics of the cable or cable combination

|              |   |
|--------------|---|
| ◦ Cable type | H07V-U 5G1.5  |
|              |  |
| ◦ Color      |   |
| ◦ Insulation | PVC   |
| ◦ CPR Class  | eca   |

### Certificates

|                     |   |
|---------------------|---|
| ◦ Norm van de buis  | EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2 |
| ◦ Norm van de kabel | IEC 60227-1; EN 50575:2014+A1:2016                                  |

### Certificates

