



BE LGN20 HF C Z1U 7G1,5 Std+ZRZW R1

Preflex SAFE 20mm+H07Z1-U Cca (a1d1s1) 7G1,5 C100

Properties of the article

◦	Articlenumber	1234000614
◦	Barcode	5420056254137
◦	Category	Energy & Light
◦	Gross weight (kg)	20.6
◦	Dimensions (WxLxH)	500 x 500 x 200 MM
◦	Packaging	Roll
◦	Length	100

Properties of the Preflex® tube

◦	Material of tube	Halogen-free Polypropylene
◦	Color	Light Green
◦	Outer diameter (mm)	20
◦	Inner diameter (mm)	14.1
◦	Classification	ICTA 3422
◦	Pressure resistance	750N / 23°C
◦	Impact resistance	6J / -5°C
◦	Breakthrough test	2000V / 50-60 Hz 15min.
◦	Insulation resistance	min. 100 Mohm/80cm
◦	Test temperature	-5°C tot +90°C
◦	Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦	Cable type	H07Z1-U 7G1.5
		
◦	Color	
◦	Insulation	LS0H
◦	CPR Class	cca s1 d1 a1

Certificates

◦	Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦	Norm van de kabel	EN 50565-1 ; EN 50565-2

Certificates

