



## BE BL20 E 2xUTP5E R1

Preflex 20mm+2xU/UTP Eca CAT5E C100

### Properties of the article

◦	Articlenumber	1234001270
◦	Barcode	5420056263948
◦	Category	Data
◦	Gross weight (kg)	13.6
◦	Dimensions (WxLxH)	500 X 500 X 200 MM
◦	Packaging	Roll
◦	Length	100

### Properties of the Preflex® tube

◦	Material of tube	Polypropylene
◦	Color	Blue
◦	Outer diameter (mm)	20
◦	Inner diameter (mm)	14.1
◦	Classification	ICTA 3422
◦	Pressure resistance	750N / 23°C
◦	Impact resistance	6J / -5°C
◦	Breakthrough test	2000V / 50-60 Hz 15min.
◦	Insulation resistance	min. 100 Mohm/80cm
◦	Test temperature	-5°C tot +90°C
◦	Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦	Cable type	U/UTP CAT5E	U/UTP CAT5E
◦	Color		
◦	Insulation		
◦	CPR Class	eca	

### Certificates

◦	Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦	Norm van de kabel	EN 50575

### Certificates

